REINER SCT Authenthicator

Hardware for secure two-factor authentication (2FA) with TOTP





Data sheet

Entering only your user name and password for a login is no longer secure nowadays. Almost all leading online platforms therefore offer the possibility of logging in with a further component.

This so-called two-factor authentication (2FA) provides a high protection level for your user account against misuse and identity theft even when your user name and password fall into the wrong hands.

The Federal Bureau for Security in Information Technology (BSI) expressly recommends the use of a two-factor authentication!

The most frequently used method is the time-based one-time password method or TOTP for short. Authenticator apps on smart phones are often used. However, the TOTP is easy to spy out here because of the limited security of smart phones.

Hardware-based TOTP generators offer maximum security. The **REINER SCT Authenticator** saves the electronic codes for the logins safely in its hardware and then generates the TOTP codes with high accuracy every 30 seconds. It works without connection to the Internet and is therefore immune to online attacks. Its function can be protected additionally by a PIN.

The **REINER SCT Authenticator** detects the authentication data displayed by the online platform in the form of a QR code in a split second by means of its built-in camera and assigns these to an account.

The highlights

- Secure two-factor authentication (2FA) with TOTP
- For smart phone, tablet, notebook or desktop
- Immediately ready to use for all leading online platforms
- Management of several TOTP accounts
- Security made in Germany

Further information under: reiner-sct.com/authenticator

REINER Kartengeräte GmbH und Co. KG | Baumannstr. 18 | D-78120 Furtwangen | Tel.: +49 (7723) 5056 0 | Fax: +49 (7723) 5056 778 | mail@reiner-sct.com

REINERSCT[®]

Technical Data | REINER SCT Authenticator

| Category and function | |
|---|---|
| Device category | Hardware TOTP generator |
| Supported processes | OATH-TOTP according to RFC 6238 |
| Supported TOTP algorithms | SHA 1, SHA 256, SHA 512 |
| Code saving | in the secure hardware chip |
| Number of TOTP accounts | 10 |
| Time synchronisation Menu functions | <u>www.reiner-sct.com/sync</u> unidirectional by means of encrypted QR Code Accounts, Reader (identification), Setting (including battery status), User PIN |
| Keyboard, camera and display | |
| Numerical keys/function keys/special keys | 10/3/2 rubber-coated keys |
| Camera | CMOS colour camera with OmniPixel3-HSTM technology, aperture angle: 57° |
| Operating display | by TFT colour display |
| Display | 1.77 inch TFT colour display 128 x 160 pixels |
| Display sector | 36 x 29 mm |
| Hardware properties | |
| Real time clock (RTC) | High-precision quartz real time clock. Average deviation < 1 ppm by auto- matic calibration in time synchronisation. Reference temperature: 25 °C |
| Real time clock backup | Backup of the real time clock for approx. 1 minute when changing the batteries |
| Code saving | in the persistent memory. The TOTP codes and accounts remain saved without battery supply. |
| Power supply | 3x alkaline-manganese batteries, size: AAA / IEC LR03, replaceable |
| Battery life | approx. 5 years (basis for calculation: 500 TOTPs per year, the actual life depends on the respective time and type of use and the ambient condi- tions) |
| Card slot | none |
| Housing colours (standard) | yellow/white |
| Special colours, customised printing | ✓ on request, minimum order quantity |
| Product dimensions (L x W x H) approx. | 102 x 62.5 x 19 mm |
| Packing dimensions (L x W x H) approx. | 201 x 149 x 47 mm |
| Weight (without/with packing) approx. | 80 g/200 g |
| Ambient temperature storage/operation | -10 °C - 50 °C/0 °C - 50 °C |
| Permissible humidity | Max. 90% no condensation |
| Vibration | 10 - 75 Hz; 10 m/s² (ISO/IEC 60068-2-6) |
| Drop test | 1 m (DIN EN 60068-2-31) |
| Conformity | CE, WEEE, RoHS2, BattG (battery law) |
| Order data/service/accessories | |
| Product name | REINER SCT Authenticator |
| REINER SCT article number | 2 708 015-000 |
| EAN-Code | 4011170084369 |
| Device packing | Four-colour printed retail box |
| Scope of supply | REINER SCT Authenticator with 3x AAA batteries and quick guide |
| Warranty | 2 years (no warranty on batteries) |
| Support | Free and proven online support under: <u>reiner-sct.com/support</u> and telepho- ne support subject to charge at +49 (900) 1001-368* |
| Design and development | Germany |
| | |

*1.50 EUR / per minute from the German fixed network. Mobile phone prices can vary. The term "QR Code" is a registered trademark of Denso Wave Incorporated. All used logos are trademarks of the respective brand owner.

Further information under: reiner-sct.com/authenticator

REINER Kartengeräte GmbH und Co. KG | Baumannstr. 18 | D-78120 Furtwangen | Tel.: +49 (7723) 5056 0 | Fax: +49 (7723) 5056 778 | mail@reiner-sct.com